

View Online at <https://aerobasegroup.com/nsn/5935-01-649-1402>

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

2.422 inches

Diameter:

0.590 inches

Overall Diameter:

1.062 inches

Cable Entrance Diameter:

0.188 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

10-6 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key or multiple key

Insert Position In Deg:

90.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms3121 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-26482 spec.