Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-649-9389

Body Style:

Straight shape, pc type

Overall Length:

253.2 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

242.2 millimeters

Overall Width:

33.3 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

12.7 millimeters

Contact Maximum Current Rating In Amps:

30.0 1st mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 1st mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

600.0 1st mating end all contact groupings

Shell Type:

Solid

Connector Locking Method:

Screw

End Application:

Uscg cutter boat, long range interceptor-ii 35ft (Iri-ii)

Terminal Location:

Front 1st mating end all contact groupings

Terminal Type:

Terminal block w/screws 1st mating end all contact groupings

Shell Material:

Plastic phenolic

Shell Surface Treatment:

Plastic phenolic

Included Contact Quantity:

16 1st mating end all contact groupings

Product Name:

Buss bar, 16-gang terminal strip (lrg); terminal block, barrier style 30a 600v 16p; terminal block - closed back 30 amps, 600 volts (ac/dc) Color:

Black

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5935-01-649-9389

Electrical Receptacle Connector - Page 2 of 2

Fiig: A039b0

