NSN 5935-01-650-5851

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-650-5851
Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.900 inches
Overall Height:
1.030 inches
Overall Width:
1.030 inches
Environmental Protection:
Shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.126 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Distance From Mounting Shoulder To Front Face:
0.470 inches
Threaded Device Type:
Threaded Device Type: Back shell and coupling facility
Back shell and coupling facility
Back shell and coupling facility Mating End Quantity:
Back shell and coupling facility Mating End Quantity: 1
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Polarization Method:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 150.0 and 210.0
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 150.0 and 210.0 Connector Locking Method:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 37p single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 and 150.0 and 210.0 Connector Locking Method: Externally threaded shell

Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

NSN 5935-01-650-5851

Electrical Receptacle Connector - Page 2 of 2



Features Provided:
Color band engagement indicator
Thready Qty Per Inch (tpi):
24
Thread Size:
0.812 inches and 0.688 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
panel thickness is 0.100 inches.
Color:
Olive drab
Precious Material And Location:
Contact plating gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
•