## NSN 5935-01-650-9178

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-650-9178 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Wall type w/ or w/o cover **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** "4, 14-20, 14-60" single mating end **Contact Maximum Current Rating In Amps:** 60.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end all contact groupings **Polarization Method:** Contact **Operating Tempurature Rating:** Between -40.0 degrees celsius and 75.0 degrees celsius **Features Provided:** Grounded contact Thready Qty Per Inch (tpi): 32 **Thread Size:** 6.0 millimeters **Terminal Location:** Back and side single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Terminal Type:** Screw single mating end all contact groupings **Shell Material:** Plastic and glass fiber **Included Contact Quantity:** 4 single mating end all contact groupings **Included Contact Type:** Flat socket single mating end 2nd contact grouping **Special Features:** The screws have 3/8 inch allen screw heads. The nema code is 14-60r.

Color:

Black

## NSN 5935-01-650-9178

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0