Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-651-0846

Thread Class:
2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.240 inches
Overall Height:
Between 1.425 inches and 1.449 inches
Overall Width:
Between 1.425 inches and 1.449 inches
Unthreaded Mounting Hole Diameter:
Between 0.120 inches and 0.136 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
Between 0.768 inches and 0.823 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-11 single mating end
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 135.0 and 170.0 and 200.0 and 310.0
Connector Locking Method:
Externally threaded shell
Features Provided:
Color band engagement indicator
Thread Size:
1.25 inches and 28.0 millimeters
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping



Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Plastic

Shell Surface Treatment:

Nickel and plastic

Thread Tolerance Class:

6g external

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Color:

Gray

Precious Material And Location:

Contact plating gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0