NSN 5935-01-652-7224

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-652-7224

Thread Direction: Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 32.5 millimeters **Overall Diameter:** Between 34.6 millimeters and 35.2 millimeters **Distance From Mounting Shoulder To Front Face:** 22.6 millimeters **Mounting Facility Thickness:** Between 1.58 millimeters and 3.20 millimeters **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 11-98 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 95.0 and 141.0 and 208.0 and 236.0 **Connector Locking Method:** Externally threaded shell **Features Provided:** Color band engagement indicator **Thread Size:** 20.0 millimeters **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum

Shell Surface Treatment:

Nickel alloy

NSN 5935-01-652-7224

Electrical Receptacle Connector - Page 2 of 2



Thread Tolerance Class:
6g external
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact plating gold
Thread Series Designator:
lso m
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0