Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-653-4003

## **Body Style:**

Angle shape, w/ or w/o cover

## **Overall Length:**

4.625 inches

# **Overall Height:**

4.375 inches

# **Overall Width:**

3.000 inches

#### **Environmental Protection:**

Corrosion resistant and dust resistant and moisture proof and waterproof

### **Unthreaded Mounting Hole Diameter:**

0.250 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

"3, 5-20" single mating end

# **Contact Maximum Current Rating In Amps:**

20.0 single mating end all contact groupings

# Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

## **Polarization Method:**

Contact

# **Connector Locking Method:**

Shell twistlock

# **Features Provided:**

Grounded contact

#### **Terminal Location:**

Side single mating end all contact groupings

# **Terminal Type:**

Screw single mating end all contact groupings

#### **Shell Material:**

Aluminum

#### Shell Surface Treatment:

Plastic

# Included Contact Quantity:

3 single mating end all contact groupings

## Included Contact Type:

T-socket single mating end 2nd contact grouping

## **Product Name:**

Hazardous area receptacle

#### **Special Features:**

Accepts 3 wires. Is 2 pole, 60 hertz receptacle. Has 0.5 inch hub. Is vapor proof. The finish is epoxy polyester.

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0