

View Online at <https://aerobasegroup.com/nsn/5935-01-653-6446>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and left-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

2.003 inches

**Overall Diameter:**

2.250 inches

**Distance From Mounting Shoulder To Front Face:**

1.156 inches

**Mounting Facility Thickness:**

Between 0.094 inches and 0.203 inches

**Threaded Device Type:**

Coupling facility and hub and back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-33 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Connector Locking Method:**

Externally threaded shell

**End Application:**

1430-01-087-6330

**Thready Qty Per Inch (tpi):**

0.1 and 18 and 18

**Thread Size:**

1.375 inches and 1.250 inches and 1.500 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel and cadmium

**Included Contact Quantity:**

11 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Product Name:**

Connector, receptacle, electrical jam nut

**Precious Material And Location:**

Contact surface silver

**Precious Material:**

Silver

**Thread Series Designator:**

Double stub and unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0