NSN 5935-01-653-9328

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-653-9328 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** Between 68.94 millimeters and 69.70 millimeters **Overall Height:** Between 18.78 millimeters and 20.28 millimeters **Overall Width:** Between 12.17 millimeters and 12.93 millimeters **Distance Between Mounting Facility Centers:** Between 63.37 millimeters and 63.63 millimeters **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Maximum Current Rating In Amps:** 7.5 single mating end all contact groupings **Polarization Method:** Mating end **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Features Provided:** Pre-tinned terminal Thready Qty Per Inch (tpi): 40 **Thread Size:** 4.0 millimeters

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold and nickel single mating end all contact groupings

Terminal Type:

Printed circuit single mating end all contact groupings

Shell Material:

Steel

NSN 5935-01-653-9328

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:	
Tin	
Included Contact Quantity:	
7 single mating end all contact groupings	
Included Contact Type:	
Round socket single mating end all contact groupings	
Precious Material And Location:	
Contact plating gold	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A039b0