NSN 5935-01-654-2137

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-654-2137 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.349 inches **Overall Height:** 1.312 inches **Overall Width:** 1.312 inches **Unthreaded Mounting Hole Diameter:** 0.128 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.469 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 17-6 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 105.0 and 132.0 and 220.0 and 265.0 and 342.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Operating Tempurature Rating:** Between 65.0 degrees celsius and 200.0 degrees celsius **Thread Size:**

0.938 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-654-2137

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per m39029/58-365
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27466 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-38999 spec.