Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-655-0366

#### **Body Style:**

Straight shape w/cover

#### **Overall Length:**

3.28 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.38 inches

#### **Overall Width:**

4.08 inches

#### **Environmental Protection:**

Watertight

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.38 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

3 single mating end

#### Contact Maximum Current Rating In Amps:

50.0 single mating end all contact groupings

## Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

#### **Polarization Method:**

Contact

#### **Connector Locking Method:**

Shell twistlock

#### **End Application:**

Boat, personnel

#### **Features Provided:**

Grounded contact

#### **Terminal Location:**

Side single mating end all contact groupings

#### **Contact Material:**

Copper alloy single mating end all contact groupings

#### **Contact Surface Treatment:**

Nickel single mating end all contact groupings

#### **Terminal Type:**

Screw single mating end all contact groupings

#### Shell Material:

Stainless steel

## Included Contact Quantity:

3 single mating end all contact groupings

#### Included Contact Type:

Curved pin single mating end 3rd contact grouping

Electrical Receptacle Connector - Page 2 of 2



**Product Name:** 

Shore power inlet

## **Special Features:**

Has a neoprene gasket in the attached cover.

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0