## NSN 5940-00-052-4579

Stud Terminal - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-052-4579

| Terminal Length:  |
|---|
| 0.283 inches  |
| Overall Height:   |
| 0.543 inches  |
| Overall Diameter:   |
| 0.255 inches  |
| Largest Diameter:   |
| 0.109 inches single end   |
| Turret Minor Diameter:  |
| 0.078 inches single end   |
| Electrical Insulation Feature:  |
| Insulating mounting bushing   |
| Mounting Method Style:  |
| Rivet   |
| Minor Bushing Diameter:   |
| 0.234 inches  |
| Major Bushing Diameter:   |
| 0.255 inches  |
| Major Bushing Length:   |
| 0.143 inches  |
| Identification Code Color:  |
| White   |
| Basic Shape Style:  |
| Nontubular, round   |
| Conductor Accommodation Type:   |
| Double turret single end  |
| Special Features:   |
| Taper pin receptacle in conductor accomodation                                      |
| Material:   |
| Plastic polytetrafluoroethylene insulation  |
| Material Specification:   |
| Qq-b-626 federal specification single material response except insulation           |
| Precious Material And Location:   |
| 1st layer conductor accommodation silver and 2nd layer conductor accommodation gold |
| Precious Material And Weight:   |
| 0.040 gold grains, troy and 0.040 silver grains, troy                               |
| Precious Material:  |
| Gold and silver   |
| Surface Treatment:  |
| Silver except insulation first layer  |
| Surface Treatment Specification:  |

Qq-s-365 type 3 federal specification 1st treatment response except insulation first layer

## NSN 5940-00-052-4579

Stud Terminal - Page 2 of 2



| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| A006b0            |

Mil-std (military Standard):

Mil-p-19468 spec.