

View Online at <https://aerobasegroup.com/nsn/5940-00-054-8960>

Mounting Hole Diameter:

0.209 inches

Dielectric Withstanding Voltage In Volts:

2100.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

1.125 inches

Distance Between Terminal Row Centers:

0.875 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.812 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.312 inches

Boardlength:

8.500 inches

Boardwidth:

2.500 inches

Boardheight:

1.687 inches

Board Height Excluding Terminals:

1.125 inches

Base Thickness:

0.625 inches

Current Rating In Amps:

90.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

6 single

Nonfeedthru Terminal Type:

598 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

6 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Surface Treatment:

Tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.