

View Online at <https://aerobasegroup.com/nsn/5940-00-057-8341>

**Mounting Hole Diameter:**

0.168 inches

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.375 inches

**Distance Between Terminal Row Centers:**

0.312 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

9.406 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.312 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.156 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.141 inches

**Boardlength:**

9.703 inches

**Boardwidth:**

0.875 inches

**Boardheight:**

0.907 inches

**Board Height Excluding Terminals:**

0.469 inches

**Base Thickness:**

0.312 inches

**Current Rating In Amps:**

7.5

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Feedthru Connection End Type:**

F4 second end single combination

**Feedthru Terminal Quantity:**

24 single combination

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Feedthru

**Material:**

Plastic diallyl phthalate board and glass fiber board

**Material Specification:**

Mil-m-2459, type gpt-30f military specification single material response board

**Surface Treatment:**

Tin terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-m-2459 spec.