

View Online at <https://aerobasegroup.com/nsn/5940-00-057-8341>

Mounting Hole Diameter:

0.168 inches

Dielectric Withstanding Voltage In Volts:

3000.0

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.375 inches

Distance Between Terminal Row Centers:

0.312 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

9.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.156 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.141 inches

Boardlength:

9.703 inches

Boardwidth:

0.875 inches

Boardheight:

0.907 inches

Board Height Excluding Terminals:

0.469 inches

Base Thickness:

0.312 inches

Current Rating In Amps:

7.5

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F4 second end single combination

Feedthru Terminal Quantity:

24 single combination

Terminal Pattern Arrangement:

Single row

Terminal Design:

Feedthru

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-m-2459, type gpt-30f military specification single material response board

Surface Treatment:

Tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-2459 spec.