NSN 5940-00-076-5845

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-076-5845

| Mounting Hole Diameter: |
|---|
| 0.156 inches |
| Dielectric Withstanding Voltage In Volts: |
| 1100.0 |
| |
| Body Style: |
| Barrier type |
| Terminal Row Quantity: |
| Center To Center Distance Between Terminals: |
| |
| 0.375 inches |
| Board Construction: |
| Hollow construction without insulated strip |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.281 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.141 inches |
| Boardlength: |
| 2.531 inches |
| Boardwidth: |
| 0.562 inches |
| Boardheight: |
| 0.718 inches |
| Board Height Excluding Terminals: |
| 0.406 inches |
| Base Thickness: |
| 0.250 inches |
| Current Rating In Amps: |
| 15.0 |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Feedthru Connection End Type: |
| 857 first end single combination |
| Feedthru Terminal Quantity: |
| 5 single combination |
| Terminal Pattern Arrangement: |
| Single row |
| Terminal Design: |
| Vertical feedthru |
| Material: |
| Plastic diallyl phthalate board and silica board |
| |

NSN 5940-00-076-5845

Terminal Board - Page 2 of 2



Material Specification:

Mil-m-14, type mdg military specification single material response board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.