

View Online at <https://aerobasegroup.com/nsn/5940-00-078-7510>

**Dielectric Withstanding Voltage In Volts:**

500.0

**Body Style:**

Strip type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.312 inches

**Distance Between Terminal Row Centers:**

1.000 inches

**Board Construction:**

Solid construction

**Boardlength:**

0.940 inches

**Boardwidth:**

0.210 inches

**Board Thickness:**

0.060 inches

**Mounting Facility Type And Quantity:**

1 friction

**Nonfeedthru Terminal Type:**

441 single

**Criticality Code Justification:**

Test

**Nonfeedthru Terminal Quantity:**

6 single

**Terminal Pattern Arrangement:**

Multi-row staggered

**Terminal Design:**

Nonfeedthru

**Material:**

Plastic board

**Precious Material And Location:**

Terminal finish gold

**Precious Material:**

Gold

**Surface Treatment:**

Gold terminals

**Test Data Document:**

35351-138127 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0