

View Online at <https://aerobasegroup.com/nsn/5940-00-105-8385>

Dielectric Withstanding Voltage In Volts:

0.7

Mounting Slot Length:

0.250 inches

Mounting Slot Width:

0.172 inches

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.438 inches

Distance Between Terminal Row Centers:

0.625 inches

Board Construction:

Constructed of interlocking pieces

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.763 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.562 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.086 inches

Boardlength:

1.984 inches

Boardwidth:

1.125 inches

Boardheight:

1.000 inches

Board Height Excluding Terminals:

0.500 inches

Base Thickness:

0.188 inches

Mounting Facility Type And Quantity:

2 slot

Terminal Connecting Link Quantity:

2 single

Nonfeedthru Terminal Type:

605 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

4 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Plastic phenolic board and cellulose board

Material Specification:

Mil-m-14, type cfg military specification single material response board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.