

View Online at <https://aerobasegroup.com/nsn/5940-00-110-2991>

Mounting Hole Diameter:

0.165 inches

Dielectric Withstanding Voltage In Volts:

1700.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.688 inches

Distance Between Terminal Row Centers:

0.625 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.188 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.594 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.219 inches

Boardlength:

6.625 inches

Boardwidth:

1.812 inches

Boardheight:

0.750 inches

Board Height Excluding Terminals:

0.750 inches

Base Thickness:

0.438 inches

Current Rating In Amps:

50.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

8 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

8 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Plastic phenolic board and cellulose board

Material Specification:

Mil-m-14, type cfg military specification single material response board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.