## NSN 5940-00-143-4611

Stud Terminal - Page 1 of 2

**Terminal Length:** 

0.250 inches



View Online at https://aerobasegroup.com/nsn/5940-00-143-4611

| 0.250 inches Overall Height: 0.969 inches Thru-hole Diameter: 0.040 inches Largest Diameter: 0.078 inches single end Electrical Insulation Feature: Standoff insulation Mounting Method Style: Stud Mounting Thread Diameter: 0.122 inches Dry Flashover Voltage Rating In Volts: 9000.0 Identification Code Color: White Thread Length: 0.219 inches Basic Shape Style: |
|--|
| 0.969 inches Thru-hole Diameter: 0.040 inches Largest Diameter: 0.078 inches single end Electrical Insulation Feature: Standoff insulation Mounting Method Style: Stud Mounting Thread Diameter: 0.122 inches Dry Flashover Voltage Rating In Volts: 9000.0 Identification Code Color: White Thread Length: 0.219 inches   |
| Thru-hole Diameter:  0.040 inches  Largest Diameter:  0.078 inches single end  Electrical Insulation Feature:  Standoff insulation  Mounting Method Style:  Stud  Mounting Thread Diameter:  0.122 inches  Dry Flashover Voltage Rating In Volts:  9000.0  Identification Code Color:  White  Thread Length:  0.219 inches   |
| 0.040 inches  Largest Diameter: 0.078 inches single end  Electrical Insulation Feature: Standoff insulation  Mounting Method Style: Stud  Mounting Thread Diameter: 0.122 inches  Dry Flashover Voltage Rating In Volts: 9000.0  Identification Code Color: White  Thread Length: 0.219 inches   |
| Largest Diameter:  0.078 inches single end  Electrical Insulation Feature:  Standoff insulation  Mounting Method Style:  Stud  Mounting Thread Diameter:  0.122 inches  Dry Flashover Voltage Rating In Volts:  9000.0  Identification Code Color:  White  Thread Length:  0.219 inches  |
| 0.078 inches single end  Electrical Insulation Feature: Standoff insulation  Mounting Method Style: Stud  Mounting Thread Diameter: 0.122 inches  Dry Flashover Voltage Rating In Volts: 9000.0  Identification Code Color: White  Thread Length: 0.219 inches   |
| Electrical Insulation Feature: Standoff insulation  Mounting Method Style: Stud  Mounting Thread Diameter: 0.122 inches  Dry Flashover Voltage Rating In Volts: 9000.0  Identification Code Color:  White  Thread Length: 0.219 inches   |
| Standoff insulation  Mounting Method Style: Stud  Mounting Thread Diameter: 0.122 inches  Dry Flashover Voltage Rating In Volts: 9000.0  Identification Code Color:  White  Thread Length: 0.219 inches  |
| Mounting Method Style: Stud  Mounting Thread Diameter: 0.122 inches  Dry Flashover Voltage Rating In Volts: 9000.0  Identification Code Color: White  Thread Length: 0.219 inches  |
| Mounting Thread Diameter:  0.122 inches  Dry Flashover Voltage Rating In Volts:  9000.0  Identification Code Color:  White  Thread Length:  0.219 inches   |
| Mounting Thread Diameter:  0.122 inches  Dry Flashover Voltage Rating In Volts: 9000.0  Identification Code Color: White  Thread Length:  0.219 inches   |
| 0.122 inches  Dry Flashover Voltage Rating In Volts: 9000.0  Identification Code Color: White  Thread Length: 0.219 inches   |
| Dry Flashover Voltage Rating In Volts: 9000.0 Identification Code Color: White Thread Length: 0.219 inches   |
| 9000.0  Identification Code Color:  White  Thread Length:  0.219 inches  |
| Identification Code Color: White Thread Length: 0.219 inches   |
| White Thread Length: 0.219 inches  |
| Thread Length: 0.219 inches  |
| 0.219 inches   |
|  |
| Basic Shape Style:   |
|  |
| Nontubular, hex  |
| Mounting Thread Series:  |
| Unc  |
| Mounting Thread Quantity:  |
| 40 per inch  |
| Conductor Accommodation Type:  |
| Pin single end   |
| Material:  |
| Copper alloy mounting facility   |
| Material Specification:  |
| L-p-395, type 1 federal specification single material response insulation  |
| Surface Treatment:   |
| Silver conductor accommodation first layer   |
| Surface Treatment Specification:   |
| Qq-p-416, ty2, cl 2 federal specification single treatment response mounting facility single layer   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

## **NSN 5940-00-143-4611** Stud Terminal - Page 2 of 2



Demilitarization:

No

Fiig:

A006b0