NSN 5940-00-143-4616

Feedthru Terminal - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-143-4616

| Width Across Flats: |
|--|
| 0.375 inches |
| Overall Height: |
| 0.874 inches |
| Largest Diameter: |
| 0.052 inches all ends |
| Turret Minor Diameter: |
| 0.035 inches all ends |
| Electrical Insulation Feature: |
| Standoff insulation |
| Mounting Method Style: |
| Threaded bushing |
| Mounting Thread Diameter: |
| 0.250 inches |
| Major Bushing Length: |
| 0.062 inches |
| Threaded Bushing Width Across Flats: |
| 0.375 inches |
| Identification Code Color: |
| Blue |
| Thread Length: |
| 0.250 inches |
| Basic Shape Style: |
| Nontubular hex |
| Mounting Thread Series: |
| Unf |
| Features Provided: |
| Mounting hardware |
| Conductor Accommodation Type: |
| Double turret all ends |
| First End Terminal Length: |
| 0.188 inches |
| Second End Terminal Length: |
| 0.188 inches |
| Material: |
| Plastic phenolic insulation |
| Material Specification: |
| Qq-b-626, 1/2 h federal specification single material response except insulation |
| Precious Material And Location: |
| Outer surface conductor accommodation silver |
| Precious Material: |

Silver

NSN 5940-00-143-4616

Feedthru Terminal - Page 2 of 2



| Sι | ırfa | се | Tr | ea | tm | en | t: |
|----|------|----|----|----|----|----|----|
| | | | | | | | |

Silver conductor accommodation single layer

Surface Treatment Specification:

Mil-f-14072, finish -311 military specification single treatment response conductor accommodation single layer

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A006b0

Mil-std (military Standard):

Mil-p-79 spec.