

View Online at <https://aerobasegroup.com/nsn/5940-00-147-8294>

Mounting Hole Diameter:

0.209 inches

Dielectric Withstanding Voltage In Volts:

1600.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.562 inches

Distance Between Terminal Row Centers:

0.500 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

11.812 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.406 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.203 inches

Boardlength:

12.218 inches

Boardwidth:

1.312 inches

Boardheight:

1.000 inches

Board Height Excluding Terminals:

0.625 inches

Base Thickness:

0.375 inches

Current Rating In Amps:

30.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

20 single

Nonfeedthru Terminal Type:

599 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

20 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Plastic phenolic and cellulose board

Material Specification:

Mil-m-14, type cfg military specification single material response board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.