

View Online at <https://aerobasegroup.com/nsn/5940-00-176-7280>

**Slot Width:**

0.041 inches single end

**Slot Depth:**

0.140 inches single end

**Terminal Length:**

0.160 inches

**Overall Height:**

0.320 inches

**Overall Diameter:**

0.120 inches

**Thru-hole Diameter:**

0.040 inches

**Largest Diameter:**

0.080 inches single end

**Electrical Insulation Feature:**

Insulating mounting bushing

**Mounting Method Style:**

Two-piece press fit

**Minor Bushing Diameter:**

0.084 inches

**Major Bushing Diameter:**

0.120 inches

**Minor Bushing Length:**

0.120 inches

**Major Bushing Length:**

0.050 inches

**Dry Flashover Voltage Rating In Volts:**

2500.0

**Identification Code Color:**

Red

**Basic Shape Style:**

Tubular, round

**Conductor Accommodation Type:**

Pin w/slot single end

**Material:**

Plastic polytetrafluoroethylene mounting facility

**Material Specification:**

Mil-p-19468 military specification single material response mounting facility

**Precious Material And Location:**

Conductor gold and conductor silver

**Precious Material And Weight:**

0.040 gold grains, troy and 0.040 silver grains, troy

**Precious Material:**

Gold and silver

**Surface Treatment:**

Silver conductor accommodation first layer

**Surface Treatment Specification:**

Qq-s-365, type 2 federal specification single treatment response conductor accommodation first layer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A006b0

**Mil-std (military Standard):**

Mil-p-19468 spec.