NSN 5940-00-177-6545

Stud Terminal - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-177-6545

| Terminal Length: |
|---|
| 0.345 inches |
| Overall Height: |
| 0.777 inches |
| Overall Diameter: |
| 0.222 inches |
| Thru-hole Diameter: |
| 0.040 inches |
| Largest Diameter: |
| 0.125 inches single end |
| Turret Minor Diameter: |
| 0.104 inches single end |
| Electrical Insulation Feature: |
| Standoff insulation |
| Mounting Method Style: |
| Swage |
| Minor Bushing Length: |
| 0.167 inches |
| Swage Depth: |
| 0.075 inches |
| Swage Outside Diameter: |
| 0.133 inches |
| Dry Flashover Voltage Rating In Volts: |
| 2500.0 |
| Identification Code Color: |
| Green |
| Basic Shape Style: |
| Nontubular, round |
| Conductor Accommodation Type: |
| Double turret single end |
| Material: |
| Copper alloy conductor accommodation |
| Material Specification: |
| L-p-395, type 1 federal specification single material response insulation |
| Surface Treatment: |
| Gold conductor accommodation first layer |
| Surface Treatment Specification: |
| Mil-g-45204, type 1, class 1 military specification single treatment response conductor accommodation first layer |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5940-00-177-6545

Stud Terminal - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A006b0

Mil-std (military Standard):

Mil-g-45204 spec.