

View Online at <https://aerobasegroup.com/nsn/5940-00-191-2746>

Mounting Hole Diameter:

0.209 inches

Dielectric Withstanding Voltage In Volts:

1600.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.562 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.375 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.203 inches

Boardlength:

3.781 inches

Boardwidth:

0.750 inches

Boardheight:

0.719 inches

Board Height Excluding Terminals:

0.719 inches

Base Thickness:

0.406 inches

Current Rating In Amps:

30.0

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonfeedthru Terminal Type:

857 first

Nonfeedthru Terminal Quantity:

5 second

Terminal Pattern Arrangement:

Single row

Terminal Design:

Nonfeedthru

Special Features:

Varnish machined ends with fungus, moisture resistant varnish

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.