NSN 5940-00-204-5086

Lug Terminal - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-00-204-5086

Overall Width: 0.141 inches Material Thickness: 0.016 inches Largest Width: 0.003 inches single end Electrical Insulation Feature: Uninsulated Mounting Method Style: Ring Mounting Method Style: Ring Mounting Tongue Width: 0.016 inches Basic Shape Style: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Sulface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig:	Overall Ler 0.438 inche				
0.141 inches Material Thickness: 0.016 inches Largest Width: 0.093 inches single end Electrical Insulation Feature: Uninsulated Mounting Method Style: Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No					
0.016 inches Largest Width: 0.093 inches single end Electrical Insulation Feature: Uninsulated Mounting Method Style: Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.141 inche	i i i i i i i i i i i i i i i i i i i			
Largest Width: 0.093 inches single end Electrical Insulation Feature: Uninsulated Mounting Method Style: Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: Na Unit Of Measure: Demilitarization: No	Material Th	ckness:			
0.93 inches single end Electrical Insulation Feature: Uninsulated Mounting Method Style: Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.193 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Sheff Life: N/a Unit Of Measure: Demilitarization: No	0.016 inche	i -			
Electrical Insulation Feature: Uninsulated Mounting Method Style: Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.193 inches Mounting Tongue Width: 0.141 inches 0.016 inches Basic Shape Style: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Sheff Life: N/a Unit Of Measure: Demilitarization: No	Largest Wi	th:			
Uninsulated Mounting Method Style: Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.141 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.093 inche	single end			
Nounting Method Style: Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Electrical I	sulation Feature:			
Ring Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Uninsulated				
Mounting Hole Diameter: 0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting M	ethod Style:			
0.093 inches Mounting Tongue Width: 0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Ring				
Mounting Tongue Width:0.141 inchesMounting Facility Thickness:0.016 inchesBasic Shape Style:SolderConductor Accommodation Type:Flat lug single endMaterial:Copper alloySurface Treatment:Tin single layerShelf Life:N/aUnit Of Measure:Demilitarization:No	Mounting H	ole Diameter:			
0.141 inches Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.093 inche	i			
Mounting Facility Thickness: 0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting 1	ongue Width:			
0.016 inches Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.141 inche	i			
Basic Shape Style: Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization:	Mounting F	acility Thickness:			
Solder Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.016 inche	i			
Conductor Accommodation Type: Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Basic Shap	e Style:			
Flat lug single end Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Solder				
Material: Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Conductor	Accommodation Type			
Copper alloy Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Flat lug sing	e end			
Surface Treatment: Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material:				
Tin single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Copper allo				
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Surface Tre	atment:			
N/a Unit Of Measure: Demilitarization: No	Tin single l	yer			
Unit Of Measure: Demilitarization: No	Shelf Life:				
 Demilitarization: No	N/a				
No	Unit Of Me	sure:			
No					
	Demilitariz	tion:			
Fiig:	No				
	Fiig:				