NSN 5940-00-204-9142

Lug Terminal - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-00-204-9142

Overall Length:
1.120 inches
Overall Width:
0.380 inches
Material Thickness:
0.043 inches
Maximum Conductor Size Accommodated:
10 awg
Electrical Insulation Feature:
Insulating sleeve
Mounting Method Style:
Ring
Mounting Hole Diameter:
0.190 inches
Mounting Tongue Width:
0.380 inches
Mounting Facility Thickness:
0.043 inches
Identification Code Color:
Yellow
Basic Shape Style:
Crimp
Crimp Conductor Accommodation Type:
·
Conductor Accommodation Type:
Conductor Accommodation Type: Recessed barrel single end
Conductor Accommodation Type: Recessed barrel single end Material:
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment:
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification:
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer Shelf Life:
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer Shelf Life: N/a
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer Shelf Life: N/a
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer Shelf Life: N/a Unit Of Measure:
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer Shelf Life: N/a Unit Of Measure: Demilitarization:
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No
Conductor Accommodation Type: Recessed barrel single end Material: Plastic polyamide insulation or plastic vinyl insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727, type 2 military specification single treatment response except insulation single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: