NSN 5940-00-241-4905

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-241-4905

| Mounting Hole Diameter: |
|---|
| 0.160 inches |
| |
| Dielectric Withstanding Voltage In Volts: 1.1 |
| |
| Body Style: |
| Barrier type |
| Terminal Row Quantity: |
| 2 |
| Center To Center Distance Between Terminals: |
| 0.375 inches |
| Distance Between Terminal Row Centers: |
| 0.312 inches |
| Board Construction: |
| Solid construction |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 8.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.312 inches |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.188 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.125 inches |
| Boardlength: |
| 8.500 inches |
| Boardwidth: |
| 0.875 inches |
| Boardheight: |
| 0.406 inches |
| Board Height Excluding Terminals: |
| 0.250 inches |
| Base Thickness: |
| 0.250 inches |
| Current Rating In Amps: |
| 15.0 |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Feedthru Connection End Type: |
| 89 15th material response both ends |
| Feedthru Terminal Quantity: |
| 21 single combination |
| Terminal Pattern Arrangement: |
| Multi-row |
| |

NSN 5940-00-241-4905

Terminal Board - Page 2 of 2

Terminal Design:

Linked nonfeedthru

Material:

Plastic board

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A011b0

