NSN 5940-00-242-6063

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-242-6063

| Mounting Hole Diameter: | | | | |
|---------------------------------------------------------------------------------|--|--|--|--|
| 0.190 inches | | | | |
| Dielectric Withstanding Voltage In Volts: | | | | |
| 0.3 | | | | |
| Body Style: | | | | |
| Barrier type | | | | |
| Terminal Row Quantity: | | | | |
| 1 | | | | |
| Center To Center Distance Between Terminals: | | | | |
| 0.438 inches | | | | |
| Board Construction: | | | | |
| Solid construction | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | |
| 5.250 inches | | | | |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: | | | | |
| 0.360 inches | | | | |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: | | | | |
| 0.188 inches | | | | |
| Boardlength: | | | | |
| 5.625 inches | | | | |
| Boardwidth: | | | | |
| 0.719 inches | | | | |
| Boardheight: | | | | |
| 1.078 inches | | | | |
| Board Height Excluding Terminals: | | | | |
| 0.531 inches | | | | |
| Base Thickness: | | | | |
| 0.312 inches | | | | |
| Current Rating In Amps: | | | | |
| 20.0 | | | | |
| Mounting Facility Type And Quantity: | | | | |
| 2 unthreaded hole | | | | |
| Feedthru Connection End Type: | | | | |
| 858 fourth combination both ends | | | | |
| Feedthru Terminal Quantity: | | | | |
| 11 single combination | | | | |
| Terminal Pattern Arrangement: | | | | |
| Single row | | | | |
| Terminal Design: | | | | |
| Vertical feedthru | | | | |
| Material: | | | | |
| Plastic board | | | | |

NSN 5940-00-242-6063

Terminal Board - Page 2 of 2



| | tment: |
|--|--------|
| | |

Tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0