NSN 5940-00-351-3298

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-351-3298

| Mounting Hole Diameter: |
|---------------------------------------------------------------------------------|
| 0.209 inches |
| Dielectric Withstanding Voltage In Volts: |
| 1600.0 |
| Terminal Row Quantity: |
| 1 |
| Center To Center Distance Between Terminals: |
| 0.562 inches |
| Board Construction: |
| Solid construction |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 7.875 inches |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.375 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.203 inches |
| Boardlength: |
| 8.281 inches |
| Boardwidth: |
| 0.750 inches |
| Boardheight: |
| 0.719 inches |
| Board Height Excluding Terminals: |
| 0.719 inches |
| Base Thickness: |
| 0.406 inches |
| Current Rating In Amps: |
| 30.0 |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Nonfeedthru Terminal Type: |
| 857 single |
| Nonfeedthru Terminal Quantity: |
| 13 single |
| Terminal Pattern Arrangement: |
| Single row |
| Terminal Design: |
| Nonfeedthru |
| Material: |
| Plastic diallyl phthalate board and glass fiber board |
| Material Specification: |

material Opecification:

Mil-p-19833, type gdi-30f military specification single material response board

NSN 5940-00-351-3298

Terminal Board - Page 2 of 2



| Surface Treatment: |
|--------------------|
| Nickel terminals |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |

Mil-std (military Standard):

Mil-p-19833 spec.