

View Online at <https://aerobasegroup.com/nsn/5940-00-405-9982>

Mounting Hole Diameter:

0.169 inches

Dielectric Withstanding Voltage In Volts:

3000.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.375 inches

Distance Between Terminal Row Centers:

0.312 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

10.906 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.281 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.141 inches

Boardlength:

11.219 inches

Boardwidth:

0.875 inches

Boardheight:

0.484 inches

Board Height Excluding Terminals:

0.484 inches

Base Thickness:

0.328 inches

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

28 single

Nonfeedthru Terminal Type:

846 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

28 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Plastic board

Surface Treatment:

Nickel terminals

Surface Treatment Specification:

Qq-n-290, class 1, type 7 federal specification single treatment response terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0