

View Online at <https://aerobasegroup.com/nsn/5940-00-433-0930>

Dielectric Withstanding Voltage In Volts:

2.5

Body Style:

T-shape

Terminal Row Quantity:

12

Center To Center Distance Between Terminals:

0.250 inches

Distance Between Terminal Row Centers:

0.312 inches

Board Construction:

Constructed of interlocking pieces

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

1.500 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

1.281 inches

Boardlength:

6.062 inches

Boardwidth:

3.000 inches

Boardheight:

5.593 inches

Base Thickness:

0.625 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

3 threaded hole

Features Provided:

Fanning holes

Mounting Facility Thread Series Designator:

Unc

Feedthru Connection End Type:

F18 both ends single combination

Feedthru Terminal Quantity:

240 single combination

Mounting Facility Thread Diameter:

0.112 inches

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Lateral feedthru

Material:

Plastic phenolic board and cellulose board

Material Specification:

Mil-m-14, type cfg military specification single material response board

Surface Treatment:

Tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.