

View Online at <https://aerobasegroup.com/nsn/5940-00-474-9896>

Mounting Hole Diameter:

0.125 inches

Dielectric Withstanding Voltage In Volts:

2000.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.250 inches

Distance Between Terminal Row Centers:

0.250 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.250 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.188 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.125 inches

Boardlength:

4.000 inches

Boardwidth:

0.625 inches

Boardheight:

0.375 inches

Board Height Excluding Terminals:

0.375 inches

Base Thickness:

0.281 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

14 single

Nonfeedthru Terminal Type:

846 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

14 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Glass fiber board

Material Specification:

Mil-m-14, sdg-f military specification single material response board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.