

View Online at <https://aerobasegroup.com/nsn/5940-00-500-5378>

Dielectric Withstanding Voltage In Volts:

2200.0

Body Style:

Barrier type

Mounting Slot Width:

0.198 inches

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.531 inches

Distance Between Terminal Row Centers:

0.812 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.875 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.906 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.250 inches

Boardlength:

3.375 inches

Boardwidth:

1.812 inches

Boardheight:

0.844 inches

Board Height Excluding Terminals:

0.781 inches

Base Thickness:

0.375 inches

Current Rating In Amps:

40.0

Mounting Facility Type And Quantity:

2 slot

Nonfeedthru Terminal Type:

599 single

Nonfeedthru Terminal Quantity:

8 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Nonfeedthru

Material:

Plastic polyester board and glass fiber board

Material Specification:

Qq-b728, class b federal specification single material response terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.