NSN 5940-00-500-5389

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-500-5389

| Mounting Hole Diameter: |
|---|
| 0.386 inches |
| Dielectric Withstanding Voltage In Volts: |
| 1.5 |
| Body Style: |
| Barrier type |
| Terminal Row Quantity: |
| 1 |
| Center To Center Distance Between Terminals: |
| 0.640 inches |
| Board Construction: |
| Hollow construction without insulated strip |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.312 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.739 inches |
| Boardlength: |
| 1.478 inches |
| Boardwidth: |
| 0.625 inches |
| Boardheight: |
| 0.688 inches |
| Board Height Excluding Terminals: |
| 0.600 inches |
| Base Thickness: |
| 0.375 inches |
| Current Rating In Amps: |
| 35.0 |
| Mounting Facility Type And Quantity: |
| 1 unthreaded hole |
| Nonfeedthru Terminal Type: |
| 600 single |
| Nonfeedthru Terminal Quantity: |
| 2 single |
| Terminal Pattern Arrangement: |
| Single row |
| Terminal Design: |
| Nonfeedthru |
| Special Markings: |
| 1, 2 |
| Material: |

Plastic polyester board and glass fiber board

NSN 5940-00-500-5389

Terminal Board - Page 2 of 2



| Material Specification: |
|---|
| Qq-b728, class b federal specification single material response terminals |
| Shelf Life: |
| N/a |

Unit Of Measure:

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.