NSN 5940-00-500-7251

Lug Terminal - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-00-500-7251

Overall Length:
1.188 inches
Overall Width:
0.469 inches
Material Thickness:
0.047 inches
Maximum Conductor Size Accommodated:
10 awg
Electrical Insulation Feature:
Uninsulated
Mounting Method Style:
Straight one hole
Mounting Hole Diameter:
0.266 inches
Mounting Tongue Width:
0.469 inches
Mounting Facility Thickness:
0.047 inches
Basic Shape Style:
Crimp
Crimp Conductor Accommodation Type:
-
Conductor Accommodation Type:
Conductor Accommodation Type: Split recessed barrel single end
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End:
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material:
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment:
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment: Tin except insulation single layer
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment: Tin except insulation single layer Shelf Life:
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a Unit Of Measure:
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a Unit Of Measure: Demilitarization:
Conductor Accommodation Type: Split recessed barrel single end Distance From Mounting Hole Center To Mounting End: 0.250 inches Material: Copper except insulation Surface Treatment: Copper except insulation single layer Shelf Life: N/a Unit Of Measure: Demilitarization: