

View Online at <https://aerobasegroup.com/nsn/5940-00-542-8546>

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Body Style:**

Barrier type

**Mounting Slot Length:**

0.210 inches

**Mounting Slot Width:**

0.180 inches

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.375 inches

**Distance Between Terminal Row Centers:**

0.500 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.750 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.438 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.188 inches

**Boardlength:**

3.125 inches

**Boardwidth:**

0.875 inches

**Boardheight:**

0.624 inches

**Board Height Excluding Terminals:**

0.500 inches

**Base Thickness:**

0.312 inches

**Current Rating In Amps:**

30.0

**Mounting Facility Type And Quantity:**

2 slot

**Terminal Connecting Link Quantity:**

6 single

**Nonfeedthru Terminal Type:**

600 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

6 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Material:**

Plastic polyester board and glass fiber board

**Material Specification:**

Qq-b728, class b federal specification single material response terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.