NSN 5940-00-587-4795

Feedthru Terminal - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-587-4795

| Overall Height: |
|--|
| 0.443 inches |
| Overall Diameter: |
| 0.150 inches |
| Largest Diameter: |
| 0.040 inches all ends |
| Electrical Insulation Feature: |
| Insulating mounting bushing |
| Mounting Method Style: |
| Press fit |
| Minor Bushing Diameter: |
| 0.125 inches |
| Major Bushing Diameter: |
| 0.150 inches |
| Minor Bushing Length: |
| 0.100 inches |
| Major Bushing Length: |
| 0.040 inches |
| Dry Flashover Voltage Rating In Volts: |
| 3000.0 |
| Identification Code Color: |
| White |
| Basic Shape Style: |
| Nontubular round |
| Conductor Accommodation Type: |
| Pin all ends |
| First End Terminal Length: |
| 0.183 inches |
| Second End Terminal Length: |
| 0.210 inches |
| Material: |
| Plastic polytetrafluoroethylene mounting facility |
| Material Specification: |
| Qq-b-626, comp 22, 1/2 hard federal specification single material response conductor accommodation |
| Precious Material And Location: |
| Inner surface silver and outer surface gold |
| Precious Material: |
| Silver and gold |
| Surface Treatment: |
| Silver conductor accommodation first layer |
| Surface Treatment Specification: |

Qq-s-365, type 1, grade b federal specification single treatment response conductor accommodation first layer

NSN 5940-00-587-4795

Feedthru Terminal - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |

Mil-std (military Standard):

Mil-p-19468 spec.