

View Online at <https://aerobasegroup.com/nsn/5940-00-604-8565>

Dielectric Withstanding Voltage In Volts:

7.5

Body Style:

Strip type

Terminal Row Quantity:

7

Center To Center Distance Between Terminals:

0.300 inches

Distance Between Terminal Row Centers:

0.320 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.820 inches

Boardlength:

7.460 inches

Boardwidth:

2.280 inches

Board Thickness:

0.125 inches

Mounting Facility Type And Quantity:

2 flange

Mounting Facility Thread Series Designator:

Unc

Feedthru Connection End Type:

435 fourth combination first combination and 442 fourth combination second combination

Nonfeedthru Terminal Type:

442 single

Feedthru Terminal Quantity:

23 single combination

Nonfeedthru Terminal Quantity:

15 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Nonfeedthru

Material:

Plastic phenolic board and paper board

Material Specification:

Qq-b-626, 1/2 h federal specification 2nd material response terminals

Precious Material And Location:

Terminals silver

Precious Material:

Silver

Surface Treatment:

Copper terminals and tin terminals and silver terminals

Surface Treatment Specification:

Mil-c-14550 military specification 1st treatment response terminals and mil-t-10727 military specification 2nd treatment response terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-c-14550 spec.