NSN 5940-00-689-6354

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-689-6354

| Mounting Hole Diameter: | | | | | | |
|---|--|--|--|--|--|--|
| 0.046 inches | | | | | | |
| Dielectric Withstanding Voltage In Volts: | | | | | | |
| 1.5 | | | | | | |
| Body Style: | | | | | | |
| Pressure-contact-rigid | | | | | | |
| Terminal Row Quantity: | | | | | | |
| 2 | | | | | | |
| Center To Center Distance Between Terminals: | | | | | | |
| 0.187 inches | | | | | | |
| Distance Between Terminal Row Centers: | | | | | | |
| 0.203 inches | | | | | | |
| Board Construction: | | | | | | |
| Solid construction | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | | | |
| 2.062 inches | | | | | | |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: | | | | | | |
| 0.235 inches | | | | | | |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: | | | | | | |
| 0.086 inches | | | | | | |
| Boardlength: | | | | | | |
| 2.234 inches | | | | | | |
| Boardwidth: | | | | | | |
| 0.509 inches | | | | | | |
| Boardheight: | | | | | | |
| 0.281 inches | | | | | | |
| Current Rating In Amps: | | | | | | |
| 10.0 | | | | | | |
| Mounting Facility Type And Quantity: | | | | | | |
| 2 unthreaded hole | | | | | | |
| Feedthru Connection End Type: | | | | | | |
| 73 15th material response both ends | | | | | | |
| Feedthru Terminal Quantity: | | | | | | |
| 10 single combination | | | | | | |
| Terminal Pattern Arrangement: | | | | | | |
| Multi-row | | | | | | |
| Terminal Design: | | | | | | |
| Feedthru | | | | | | |
| Special Features: | | | | | | |
| Double screw term, mounter in foursided busbar assembly | | | | | | |
| Material: | | | | | | |
| Plastic board | | | | | | |

NSN 5940-00-689-6354

Terminal Board - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0