NSN 5940-00-716-6680

Stud Terminal - Page 1 of 2

Terminal Length:



View Online at https://aerobasegroup.com/nsn/5940-00-716-6680

| 0.160 inches |
|--|
| Width Across Flats: |
| 0.188 inches |
| Overall Height: |
| 0.414 inches |
| Largest Diameter: |
| 0.062 inches single end |
| Turret Minor Diameter: |
| 0.031 inches single end |
| Electrical Insulation Feature: |
| Insulating sleeve |
| Mounting Method Style: |
| Press fit |
| Minor Bushing Diameter: |
| 0.115 inches |
| Major Bushing Diameter: |
| 0.188 inches |
| Minor Bushing Length: |
| 0.054 inches |
| Major Bushing Length: |
| 0.200 inches |
| Dry Flashover Voltage Rating In Volts: |
| 1000.0 |
| Identification Code Color: |
| Green |
| Basic Shape Style: |
| Nontubular, hex |
| Conductor Accommodation Type: |
| Double turret single end |
| Material: |
| Copper alloy conductor accommodation |
| Material Specification: |
| Qq-b-626, 1/2h federal specification single material response mounting facility |
| Surface Treatment: |
| Silver conductor accommodation first layer |
| Surface Treatment Specification: |
| Qq-p-416, ty1, cl 2 federal specification single treatment response mounting facility single layer |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5940-00-716-6680

Stud Terminal - Page 2 of 2



| _ | | | | | | | | | | |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | 2 | iza | 31 | ^ | n | |
| | | | | | | | | | | |

No

Fiig:

A006b0

Mil-std (military Standard):

Mil-g-45204 spec.