

View Online at <https://aerobasegroup.com/nsn/5940-00-725-7252>

**Dielectric Withstanding Voltage In Volts:**

2.2

**Body Style:**

Barrier type

**Mounting Slot Length:**

0.218 inches

**Mounting Slot Width:**

0.173 inches

**Terminal Row Quantity:**

1

**Center To Center Distance Between Terminals:**

0.375 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.000 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.312 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.250 inches

**Boardlength:**

2.500 inches

**Boardwidth:**

0.625 inches

**Boardheight:**

1.125 inches

**Board Height Excluding Terminals:**

1.000 inches

**Base Thickness:**

0.500 inches

**Current Rating In Amps:**

40.0

**Mounting Facility Type And Quantity:**

2 slot

**Feedthru Connection End Type:**

599 fourth combination both ends

**Feedthru Terminal Quantity:**

4 single combination

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Vertical feedthru

**Material:**

Plastic polyester board and glass fiber board

**Material Specification:**

Qq-b728, class b federal specification single material response terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.