NSN 5940-00-737-3587

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-737-3587

Dielectric Withstanding Voltage In Volts: 2.0 Body Style: Barrier type Terminal Row Quantity: 1 Center To Center Distance Between Terminals: 0.250 inches Board Construction Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardheight: 0.375 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Board Height Exclud		
Delectric Withstanding Voltage In Volts: 2.0 Body Style: Barrier type Terminal Row Quantity: 1 Center To Center Distance Between Terminals: 0.250 inches Board Construction: Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Facility: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.203 inches Boardlength: 0.206 inches Boardheight: 0.375 inches Boardheight: 0.375 inches Boardheight Excluding Terminals: 0.375 inches Board Height Excluding Terminals: 0.375 inches Board Height Excluding Terminals: 0.375 inches Boardheight: 0.375 inches 0.375 inches Boardheight: 0.375 inches Boardheight: 0.375 inches Boardheight: 0.375 inches Boardheight: 0.375 inches Boardh	-	
2.0 Body Style: Barrier type Terminal Row Quantity: 1 Center To Center Distance Between Terminals: 2.200 inches Board Construction Conter To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Facility: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.375 inches Boardwidth: 0.375 inches Base Thickness: 0.375 inches Base Thickness: 0.375 inches Base Thickness: 0.326 inches Base Thickness: 0.321 inches Base Thickness: 0.325 inches Base Thickness: 0.325 inches Base Thickness: 0.326 inches Base Thickness: 0.327 inches Base Thickness: 0.328 inches Base Thickness: 0.329 inches Distance Terminal Davity: 1.4 singl Terminal Davity: 1.4 singl T	0.125 inches	
Body Style: Barier type Terminal Row Quantity: 1 Center To Center Distance Between Terminals: 0.250 inches Board Construction: Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.203 inches Board Height 8.000 inches Board Height 8.000 inches Board Height Excluding Terminals: 0.375 inches Board Height Excluding Terminal Termin	Dielectric Withstanding Voltage In Volts:	
Barier type Terminal Row Quantity: 1 Center To Center Distance Between Terminals: 0.250 inches Board Construction: Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of Mounting Facilities Boardlength: 0.250 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.281 inches Base Thickness: 0.281 inches Current Rating In Amps: 3.0 Mounting Facility Type And Quantity: 2 unthreaded hole Norfeedthru Terminal Type: 857 single Norfeedthru Terminal Quantity: 14 single Terminal Design: Norfeedthru	2.0	
Terminal Row Quantity: 1 Center To Center Distance Between Terminals: 0.250 inches Board Construction: Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Bottom Edge Of Terminal Board To Center Of First Mounting Facility: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.251 inches Boardlength: 4.000 inches Boardheight: 0.406 inches Boardheight Excluding Terminals: 0.375 inches Board Height Excluding Terminal Board Terminal Patern Arrangement: Single row Terminal Design: Nonfeedthru Height Excluding Height Exclud	Body Style:	
1 Center To Center Distance Between Terminals: 0.250 inches Board Construction: Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardwidth: 0.406 inches Board Hight Excluding Terminals: 0.375 inches Board Hight Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 3.0 Mounting Facility Type And Quantity: 2 unthreaded hole Norfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Norfeedthru	Barrier type	
Center To Center Distance Between Terminals: 0.250 linches Board Construction: Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 linches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 linches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.203 linches Boardlength: 4.000 linches Boardwidth: 0.406 linches Boardheight: 0.375 linches Board Height Excluding Terminals: 0.375 linches Base Thickness: 0.281 linches Current Rating In Amps: 5.0 Monfeedthru Terminal Type: 8.7 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	Terminal Row Quantity:	
0.250 linches Board Construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 linches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 linches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 linches Boardlength: 0.000 linches Boardthit: 0.406 linches Boardheight: 0.375 linches Board Height Excluding Terminals: 0.375 linches Base Thickness: 0.281 linches Current Rating In Amps: 5.0 Monfeedthru Terminal Type: 2.37 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	1	
Board Construction: Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Leff Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardheight: 0.406 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	Center To Center Distance Between Terminals:	
Solid construction Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardwidth: 0.406 inches Boardheight Excluding Terminals: 0.375 inches Base Thickness: 0.375 inches Base Thickness: 0.281 inches 2.0 Untreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	0.250 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardwidth: 0.406 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	Board Construction:	
3750 inches Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	Solid construction	
Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: 0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardwidth: 0.406 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	Center To Center Distance Between Mounting Facilities P	arallel To Length:
0.203 inches Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardheight: 0.406 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Norfeedthru Terminal Type: 857 single Norfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Norfeedthru	3.750 inches	
Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: 0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardheight: 0.406 inches Boardheight Excluding Terminals: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	Distance From Bottom Edge Of Terminal Board To Center	Of Mounting Hole:
0.125 inches Boardlength: 4.000 inches Boardwidth: 0.406 inches Boardwidth: 0.406 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	0.203 inches	
Boardength:4.000 inchesBoardwidth:0.406 inchesBoardheight:0.375 inchesBoard Height Excluding Terminals:0.375 inchesBase Thickness:0.375 inchesBase Thickness:0.281 inchesCurrent Rating In Amps:5.0Mounting Facility Type And Quantity:2 unthreaded holeNonfeedthru Terminal Type:857 singleNonfeedthru Terminal Quantity:14 singleTerminal Pattern Arrangement:Single rowTerminal Design:NonfeedthruKonfeedthruHerinal Pattern Arrangement:Single rowTerminal Design:NonfeedthruNonfeedthruKatrial:NonfeedthruNonfeedthruSingle rowSingle	Distance From Left Edge Of Terminal Board To Center Of	First Mounting Facility:
4.000 inches Boardwidth: 0.406 inches Boardwidth: 0.406 inches Boardweight: 0.406 inches Boardweight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 0.281 inches Current Rating In Amps: 0.281 inches Current Rating In Amps: 0.30 Mounting Facility Type And Quantity: 0.315 inches Single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	0.125 inches	
Boardwidth: 0.406 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Single row Terminal Design: Nonfeedthru	Boardlength:	
0.406 inches Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.375 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	4.000 inches	
Boardheight: 0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	Boardwidth:	
0.375 inches Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	0.406 inches	
Board Height Excluding Terminals: 0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	Boardheight:	
0.375 inches Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	0.375 inches	
Base Thickness: 0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	Board Height Excluding Terminals:	
0.281 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	0.375 inches	
Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	Base Thickness:	
5.0 Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	0.281 inches	
Mounting Facility Type And Quantity: 2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	Current Rating In Amps:	
2 unthreaded hole Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	5.0	
Nonfeedthru Terminal Type: 857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru	Mounting Facility Type And Quantity:	
857 single Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	2 unthreaded hole	
Nonfeedthru Terminal Quantity: 14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	Nonfeedthru Terminal Type:	
14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	857 single	
14 single Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:	Nonfeedthru Terminal Quantity:	
Terminal Pattern Arrangement: Single row Terminal Design: Nonfeedthru Material:		
Single row Terminal Design: Nonfeedthru Material:		
Terminal Design: Nonfeedthru Material:	-	
Nonfeedthru Material:	-	
Material:		

NSN 5940-00-737-3587

Terminal Board - Page 2 of 2



Material Specification:

Mil-m-14, sdg-f military specification single material response board

Surface Treatment:

Nickel terminals

Surface Treatment Specification:

Qq-n-290, class 1, type 7 federal specification single treatment response terminals

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.