

View Online at <https://aerobasegroup.com/nsn/5940-00-769-3518>

**Mounting Hole Diameter:**

0.125 inches

**Dielectric Withstanding Voltage In Volts:**

3.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.250 inches

**Distance Between Terminal Row Centers:**

0.250 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.250 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.188 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.125 inches

**Boardlength:**

2.250 inches

**Boardwidth:**

0.625 inches

**Boardheight:**

0.625 inches

**Board Height Excluding Terminals:**

0.312 inches

**Base Thickness:**

0.219 inches

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Feedthru Connection End Type:**

F4 15th material response both ends

**Feedthru Terminal Quantity:**

7 single combination

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Feedthru

**Material:**

Plastic phenolic board

**Surface Treatment:**

Nickel terminals and tin terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0