

View Online at <https://aerobasegroup.com/nsn/5940-00-777-4222>

**Mounting Hole Diameter:**

0.160 inches

**Dielectric Withstanding Voltage In Volts:**

1.1

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.375 inches

**Distance Between Terminal Row Centers:**

0.312 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.844 inches and 1.891 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.312 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.281 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.148 inches

**Boardlength:**

2.172 inches

**Boardwidth:**

0.875 inches

**Boardheight:**

0.406 inches

**Board Height Excluding Terminals:**

0.406 inches

**Base Thickness:**

0.250 inches

**Current Rating In Amps:**

15.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

4 single

**Nonfeedthru Terminal Type:**

857 single

**Terminal Connecting Link Type:**

2 single

**Nonfeedthru Terminal Quantity:**

8 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Special Features:**

Phillips head screw terminals

**Material:**

Plastic diallyl phthalate board and plastic acrylic board

**Surface Treatment:**

Nickel terminals

**Reference Number Differentiating Characteristics:**

Quality controlled forpolaris

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0