

View Online at <https://aerobasegroup.com/nsn/5940-00-777-4222>

Mounting Hole Diameter:

0.160 inches

Dielectric Withstanding Voltage In Volts:

1.1

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.375 inches

Distance Between Terminal Row Centers:

0.312 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.844 inches and 1.891 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.281 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.148 inches

Boardlength:

2.172 inches

Boardwidth:

0.875 inches

Boardheight:

0.406 inches

Board Height Excluding Terminals:

0.406 inches

Base Thickness:

0.250 inches

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

4 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

2 single

Nonfeedthru Terminal Quantity:

8 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Special Features:

Phillips head screw terminals

Material:

Plastic diallyl phthalate board and plastic acrylic board

Surface Treatment:

Nickel terminals

Reference Number Differentiating Characteristics:

Quality controlled forpolaris

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0