

View Online at <https://aerobasegroup.com/nsn/5940-00-789-1809>

Dielectric Withstanding Voltage In Volts:

1.5

Body Style:

Barrier type

Mounting Slot Width:

0.201 inches

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.443 inches

Distance Between Terminal Row Centers:

0.688 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.719 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.250 inches

Boardlength:

6.500 inches

Boardwidth:

1.438 inches

Boardheight:

0.812 inches

Board Height Excluding Terminals:

0.625 inches

Base Thickness:

0.375 inches

Current Rating In Amps:

30.0

Mounting Facility Type And Quantity:

2 slot

Nonfeedthru Terminal Type:

599 single

Criticality Code Justification:

Zzzy

Nonfeedthru Terminal Quantity:

24 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Nonfeedthru

Special Features:

No 8-32 nc-2 thread studs

Special Markings:

1234-56-789-1011

Material:

Plastic board and glass board

Test Data Document:

56232-1-1653793 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Reference Number Differentiating Characteristics:

Quality controlled for polaris

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0