

View Online at <https://aerobasegroup.com/nsn/5940-00-789-1809>

**Dielectric Withstanding Voltage In Volts:**

1.5

**Body Style:**

Barrier type

**Mounting Slot Width:**

0.201 inches

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.443 inches

**Distance Between Terminal Row Centers:**

0.688 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.000 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.719 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.250 inches

**Boardlength:**

6.500 inches

**Boardwidth:**

1.438 inches

**Boardheight:**

0.812 inches

**Board Height Excluding Terminals:**

0.625 inches

**Base Thickness:**

0.375 inches

**Current Rating In Amps:**

30.0

**Mounting Facility Type And Quantity:**

2 slot

**Nonfeedthru Terminal Type:**

599 single

**Criticality Code Justification:**

Zzzy

**Nonfeedthru Terminal Quantity:**

24 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Nonfeedthru

**Special Features:**

No 8-32 nc-2 thread studs

**Special Markings:**

1234-56-789-1011

**Material:**

Plastic board and glass board

**Test Data Document:**

56232-1-1653793 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Reference Number Differentiating Characteristics:**

Quality controlled for polaris

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0