

View Online at <https://aerobasegroup.com/nsn/5940-00-792-3775>

**Dielectric Withstanding Voltage In Volts:**

0.6

**Body Style:**

Barrier type

**Terminal Row Quantity:**

1

**Center To Center Distance Between Terminals:**

0.594 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.875 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.531 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.250 inches

**Boardlength:**

7.375 inches

**Boardwidth:**

1.062 inches

**Boardheight:**

0.938 inches

**Board Height Excluding Terminals:**

0.875 inches

**Base Thickness:**

0.500 inches

**Mounting Facility Type And Quantity:**

2 slot

**Nonfeedthru Terminal Type:**

597 single

**Nonfeedthru Terminal Quantity:**

10 single

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Nonfeedthru

**Special Features:**

Mtg hole for no. 10 screw; 10 no. 8-32 nc-2b stud nuts inserts furnished

**Material:**

Plastic polyester board and glass fiber board

**Material Specification:**

Mil-m-14 military specification all material responses board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.