## NSN 5940-00-802-7694

Conductor Splice - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-00-802-7694

| Overall Length:  1.000 inches  Maximum Conductor Size Accommodated:  10 awg  Electrical Insulation Feature: Insulating sleeve Identification Code Color: Yellow  Basic Shape Style: Crimp  Conductor Accommodation Type: Straight barrel single end  Special Features: Arequires adapter sleeve for wire combinations 4 conductors no. 22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material: Plastic polyamide insulation  Surface Treatment: Tin except insulation single layer  Shelf Life: N/a  Unit Of Measure: |        |
|--|--------|
| Maximum Conductor Size Accommodated:  10 awg  Electrical Insulation Feature: Insulating sleeve Identification Code Color: Yellow  Basic Shape Style: Crimp  Conductor Accommodation Type: Straight barrel single end  Special Features: Arequires adapter sleeve for wire combinations 4 conductors no. 22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material: Plastic polyamide insulation  Surface Treatment: Tin except insulation single layer  Shelf Life: N/a  |        |
| Electrical Insulation Feature: Insulating sleeve Identification Code Color: Yellow Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Special Features: Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg Material: Plastic polyamide insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a   |        |
| Electrical Insulation Feature: Insulating sleeve Identification Code Color: Yellow Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Special Features: Arequires adapter sleeve for wire combinations 4 conductors no. 22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg Material: Plastic polyamide insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a  |        |
| Insulating sleeve  Identification Code Color:  Yellow  Basic Shape Style: Crimp  Conductor Accommodation Type: Straight barrel single end  Special Features: Arequires adapter sleeve for wire combinations 4 conductors no. 22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material: Plastic polyamide insulation  Surface Treatment: Tin except insulation single layer  Shelf Life: N/a   |        |
| Identification Code Color: Yellow Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Special Features: Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg Material: Plastic polyamide insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a  |        |
| Yellow  Basic Shape Style: Crimp  Conductor Accommodation Type: Straight barrel single end  Special Features: Arequires adapter sleeve for wire combinations 4 conductors no. 22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material: Plastic polyamide insulation  Surface Treatment: Tin except insulation single layer  Shelf Life: N/a  |        |
| Basic Shape Style: Crimp  Conductor Accommodation Type: Straight barrel single end  Special Features: Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 conno. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material: Plastic polyamide insulation  Surface Treatment: Tin except insulation single layer  Shelf Life: N/a  |        |
| Crimp  Conductor Accommodation Type: Straight barrel single end  Special Features: Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material: Plastic polyamide insulation  Surface Treatment: Tin except insulation single layer  Shelf Life: N/a  |        |
| Conductor Accommodation Type:  Straight barrel single end  Special Features:  Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material:  Plastic polyamide insulation  Surface Treatment:  Tin except insulation single layer  Shelf Life:  N/a  |        |
| Straight barrel single end  Special Features:  Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material:  Plastic polyamide insulation  Surface Treatment:  Tin except insulation single layer  Shelf Life:  N/a   |        |
| Special Features:  Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material:  Plastic polyamide insulation  Surface Treatment:  Tin except insulation single layer  Shelf Life:  N/a   |        |
| Arequires adapter sleeve for wire combinations 4 conductors no.22 awg., 4 conductors no. 20 awg., 4 conductors no. 18 awg., 3 con no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material:  Plastic polyamide insulation  Surface Treatment:  Tin except insulation single layer  Shelf Life:  N/a  |        |
| no. 16 awg., 2 conductors no. 14 awg., 1 conductors no. 12 awg  Material:  Plastic polyamide insulation  Surface Treatment:  Tin except insulation single layer  Shelf Life:  N/a  |        |
| Material: Plastic polyamide insulation Surface Treatment: Tin except insulation single layer Shelf Life: N/a   | uctors |
| Plastic polyamide insulation  Surface Treatment:  Tin except insulation single layer  Shelf Life:  N/a   |        |
| Surface Treatment: Tin except insulation single layer Shelf Life: N/a  |        |
| Tin except insulation single layer  Shelf Life: N/a  |        |
| Shelf Life:<br>N/a   |        |
| N/a  |        |
|  |        |
| Unit Of Measure:   |        |
|  |        |
| <del></del>  |        |
| Demilitarization:  |        |
| No No  |        |
| Fiig:  |        |
| A006b0   |        |